



**Cylinder 290 STEMT** H: 13.25 W: 8 OAL: 27.75

### Description

8" diameter cylinder, suspended by 12" stem with 40° swivel canopy  
Designed for use with uni-directional LED or reflector type (R/PAR) lamps

### Specifications

**Housing** Spun aluminum cylinder with stamped steel canopy

**Diffuser/Optics** Clear tempered glass bottom lens

**Light Source** MBL Medium Base

**Max Watts** 25 120

**Electrical** MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.  
MBL - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.

**Mounting** Mounts over 4" recessed outlet box.

**Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations



**Ordering Guide:** Choose from each category, using designated code to specify.

290 STEMT				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

#### Diffuser/Optics

Clear tempered glass

#### Light Source

**MBL15 PAR FL** - 15W/30K 1200 Lm PAR38  
**MBL15 PAR SP** - 15W/30K 1200 Lm PAR38  
**MBL15 PAR WFL** - 15W/30K 1200 Lm PAR38  
**MBL18 PAR FL** - 18W/30K 1400 Lm PAR38  
**MB25 PAR** - 25W MAX. MED base (Par38 lamp by others)  
**MB** - Maximum 120W Par38 (by others)

#### Finish

**Standard**  
**BL** - Black  
**DB** - Dura-Bronze  
**WH** - White  
**Upgraded\***  
**RAL** - Specify Color #  
**UPG** - Select Color from Luraline Palette  
**Premium\***  
**CCM** - Custom Color  
**CIC** - Inner Color  
**CTC** - Clear Top Coat  
 \* Subject to Surcharge

#### Extras (Order Separately)

**B90** Black milli-groove baffle (Not Available with Tempered glass lens)  
**SSP 120** 4KV 120V MOV1 Surge Suppressor