



Cylinder 290 WMX H: 12.88 W: 8 E: 12.50 MC: 4

Description

8" Diameter Downlight cylinder wall-mount

Specifications

- Housing** Spun aluminum cylinder with die-cast arm/back*
- Diffuser/Optics** • Bare lamp (open aperture)
• Reflector
- Light Source** LED
- Max Watts** 36.12
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - For dry locations only

Ordering Guide: Choose from each category, using designated code to specify.

290 WMX				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

- Bare lamp (open aperture) - For LENSED aperture, see Model No. 290 WMXT
- R** - Flood Reflector

Light Source

- TL16 HO** - 15.94W/40K 3320 Lm, 120V dimmable
- TL16** - 16.41W/30K 2895 Lm, 120V dimmable
- TL19 HO** - 19.3W/40K 3871 Lm, 120V dimmable
- TL20** - 19.9W/30K 3421 Lm, 0-10V dimmable
- TL23 HO** - 22.71W/40K 4410 Lm, 0-10V dimmable
- TL23** - 23.41W/30K 3931 Lm, 0-10V dimmable
- TL26 HO** - 26.16W/40K 4938 Lm, 0-10V dimmable
- TL27** - 26.98W/30K 4428 Lm, 0-10V dimmable
- TL30 HO** - 29.65W/40K 5455 Lm, 0-10V dimmable
- TL31** - 30.6W/30K 4913 Lm, 0-10V dimmable
- TL35 HO** - 34.95W/40K 6213 Lm, 0-10V dimmable
- TL36** - 36.12W/30K 5620 Lm, 0-10V dimmable

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 27K** Non-Stock item - consult factory for availability
- 35K** Neutral White
- DIM010** 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP** 10KV 120-277V Supplemental Surge Protection

NOTES:
*Driver is housed in extended aluminum canopy (not shown)