



**Cylinder 290 WMXT** H: 13.19 W: 8 E: 12.50 MC: 4

**Description**

8" Diameter Downlight cylinder wall-mount

**Specifications**

- Housing** Spun aluminum cylinder with die-cast arm/back
- Diffuser/Optics** Clear tempered glass bottom lens
- Light Source** LED
- Max Watts** 36.12
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations



**Ordering Guide:** Choose from each category, using designated code to specify.

290 WMXT					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

**Diffuser/Optics**

Clear tempered glass

**Light Source**

- TL16 HO - 15.94W/40K 3320 Lm, 120V dimmable
- TL16 - 16.41W/30K 2895 Lm, 120V dimmable
- TL19 HO - 19.3W/40K 3871 Lm, 120V dimmable
- TL20 - 19.9W/30K 3421 Lm, 0-10V dimmable
- TL23 HO - 22.71W/40K 4410 Lm, 0-10V dimmable
- TL23 - 23.41W/30K 3931 Lm, 0-10V dimmable
- TL26 HO - 26.16W/40K 4938 Lm, 0-10V dimmable
- TL27 - 26.98W/30K 4428 Lm, 0-10V dimmable
- TL30 HO - 29.65W/40K 5455 Lm, 0-10V dimmable
- TL31 - 30.6W/30K 4913 Lm, 0-10V dimmable
- TL35 HO - 34.95W/40K 6213 Lm, 0-10V dimmable
- TL36 - 36.12W/30K 5620 Lm, 0-10V dimmable

**Finish**

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded\***
- RAL - Specify Color #
- UPG - Select Color from Luraline Palette
- Premium\***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**

- 27K Non-Stock item - consult factory for availability
- 35K Neutral White
- B90 Black milli-groove baffle (Not Available with Tempered glass lens)
- DIM010 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP 10KV 120-277V Supplemental Surge Protection

NOTES: \*Driver is housed in extended aluminum canopy (not shown)  
 \*Driver is housed in extended aluminum canopy (not shown)  
 \*Driver is housed in extended aluminum canopy (not shown)  
 \*Driver is housed in extended aluminum canopy (not shown)  
 \*Driver is housed in extended aluminum canopy (not shown)  
 \*Driver is housed in extended aluminum canopy (not shown)