



Decorative 712 STEM H: 12 W: 12 OAL: 25

Description

12" Globe pendant with 12" stem and 40° swivel canopy

Specifications

Housing	Stamped steel slip fitter and canopy		
Diffuser/Optics	WACS - Seamless White Acrylic		
Light Source	GUL	MBL	Medium Base
Max Watts	15	18	100
Electrical	MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. MBL - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures. GUL - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.		
Mounting	Mounts over 4" recessed outlet box.		
Certification	Manufactured in accordance with U.L. standard 1598 - For dry locations only		

Ordering Guide: Choose from each category, using designated code to specify.

712 STEM					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

WACS - 1-piece White Acrylic (blow-molded)

Light Source

MB25 A - 25W MAX. MED base (A19 lamp by others)
MBL6A - 5.5W/30K 470 Lm OmniLED
MBL9.8A - 9.8W/30K 800 Lm OmniLED
MBL10A JAB - 10W/30K 800 Lm 90+ CRI OmniLED
MBL11A - 11W/30K 1100 Lm OmniLED
GUL11A - 11W/27K 1100 Lm GU24 OmniLED
MBL13A JAB - 13W/30K 1100 Lm 90+ CRI OmniLED
MBL15A - 15W/30K 1600 Lm OmniLED
GUL15A - 15W/27K 1600 Lm GU24 OmniLED
MBL18A JAB - 18W/30K 1600 Lm 90+ CRI OmniLED
MB - 100W Max Incand A (by others)

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

SSP 120 4KV 120V MOV1 Surge Suppressor

NOTES: When illuminated by certain light sources, a "shadow" may be visible at the bottom of Seamless White Acrylic globes (WACS). This is a result of the rotational molding process, NOT a manufacturing defect.