



**Decorative 718 STEM** H: 18 W: 18 OAL: 31

**Description**

18" Globe pendant with 12" stem and 40° swivel canopy

**Specifications**

<b>Housing</b>	Stamped steel fitter and canopy		
<b>Diffuser/Optics</b>	WACS - Seamless White Acrylic		
<b>Light Source</b>	GUL	MBL	Medium Base
<b>Max Watts</b>	15	15	150
<b>Electrical</b>	<b>MB</b> - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. <b>MBL</b> - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures. <b>GUL</b> - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.		
<b>Mounting</b>	Mounts over 4" recessed outlet box.		
<b>Certification</b>	Manufactured in accordance with U.L. standard 1598 - For dry locations only		

**Ordering Guide:** Choose from each category, using designated code to specify.

718 STEM					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

**Diffuser/Optics**

**WACS** - 1-piece White Acrylic (blow-molded)

**Light Source**

**GUL11A** - 11W/27K 1100 Lm GU24 OmniLED  
**MBL11A** - 11W/30K 1100 Lm OmniLED  
**MBL15A** - 15./30K 1600 Lm OmniLED  
**GUL15A** - 15W/27K 1600 Lm GU24 OmniLED  
**MB** - 150W Max Incand A (by others)

**Finish**

**Standard**  
**BL** - Black  
**DB** - Dura-Bronze  
**WH** - White  
**Upgraded\***  
**RAL** - Specify Color #  
**UPG** - Select Color from Luraline Palette  
**Premium\***  
**CCM** - Custom Color  
**CIC** - Inner Color  
**CTC** - Clear Top Coat  
 \* Subject to Surcharge

**Extras (Order Separately)**

**SSP 120** 4KV 120V MOV1 Surge Suppressor

NOTES: When illuminated by certain light sources, a "shadow" may be visible at the bottom of Seamless White Acrylic globes (WACS). This is a result of the rotational molding process, NOT a manufacturing defect.