



**Decorative ABC24HB** H: 8 W: 24 OAL: 36

**Description**

Cable-hung 24" Acrylic Bowl pendant with half-ball trim

**Specifications**

<b>Housing</b>	Mixed metals				
<b>Diffuser/Optics</b>	<ul style="list-style-type: none"> <li>• FAL - Faux-Alabaster Acrylic</li> <li>• Satin Opal Acrylic</li> <li>• WAC - White Acrylic</li> </ul>				
<b>Light Source</b>	GUL	LTE	MBL	Medium Base LTE	
<b>Max Watts</b>	15.5 X 3	11.4 X 3	15.5 X 3	150 X 3	11.4 X 6
<b>Electrical</b>	<p><b>MB</b> - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.</p> <p><b>MBL</b> - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.</p> <p><b>GUL</b> - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.</p> <p><b>LTE</b> - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.</p>				
<b>Mounting</b>	Mounts over 4" recessed outlet box.				
<b>Certification</b>	Manufactured in accordance with U.L. standard 1598 - For dry locations only				



**Ordering Guide:** Choose from each category, using designated code to specify.

ABC24HB					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

**Diffuser/Optics**

- FAL** - Faux-Alabaster Acrylic
- WAC** - White Acrylic
- SOA** - Satin Opal Acrylic

**Light Source**

- 3L11 LTE** - 34.2W/30K 4890 Lm LED
- 6L11 LTE** - 68.4W/30K 9780 lumen LED
- 3GUL15.5 A21** - 46.5W/27K 4800 Lm GU24 OmniLED
- 3MBL15.5 A21** - 46.5W/30K 4950 Lm OmniLED
- MB** - Maximum 3x 150W A (by others)

**Finish**

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded\***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium\***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**

- 2DIM010** LED 4-wire 0-10V Dimming - 120-277V
- SSP** 10KV 120-277V Supplemental Surge Protection