



Decorative **ABR24HB** H: 8 W: 24 OAL: 36

Description

Rod-hung 24" Acrylic Bowl pendant with half-ball trim

Specifications

Housing	Mixed metals			
Diffuser/Optics	<ul style="list-style-type: none"> • FAL - Faux-Alabaster Acrylic • SOA - Satin Opal Acrylic • WAC - White Acrylic 			
Light Source	GUL	LTE	MBL	Medium Base
Max Watts	15.5 X 3	11.4 X 3	15.5 X 3	150 X 3
Electrical	<p>MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.</p> <p>MBL - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.</p> <p>GUL - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.</p> <p>LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.</p>			
Mounting	Mounts over 4" recessed outlet box.			
Certification	Manufactured in accordance with U.L. standard 1598 - For dry locations only			



Ordering Guide: Choose from each category, using designated code to specify.

ABR24HB					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

FAL - Faux-Alabaster Acrylic
SOA - Satin Opal Acrylic
WAC - White Acrylic

Light Source

3L11 LTE - 34.2W/30K 4890 Lm LED
3GUL15.5 A21 - 46.5W/27K 4800 Lm GU24 OmniLED
3MBL15.5 A21 - 46.5W/30K 4950 Lm OmniLED
MB - Maximum 3x 150W A (by others)

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

2DIM010 LED 4-wire 0-10V Dimming - 120-277V
BBL 90 minutes Battery Backup - For LED only (100- 277V/50-60Hz Input Voltage)
SSP 10KV 120-277V Supplemental Surge Protection