




ABR30[®]
shown



Decorative ABR36HB H: 11 W: 36 OAL: 35

Description

Rod-hung 36" Acrylic Bowl pendant with half-ball trim

Specifications

Housing	Mixed metals
Diffuser/Optics	<ul style="list-style-type: none"> • FAL - Faux-Alabaster Acrylic • SOA - Satin Opal Acrylic • WAC - White Acrylic
Light Source	LTE Medium Base
Max Watts	11.4 X 6 150 X 6
Electrical	MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.
Mounting	Mounts over 4" recessed outlet box.
Certification	Manufactured in accordance with U.L. standard 1598 - For dry locations only



Ordering Guide: Choose from each category, using designated code to specify.

ABR36HB					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

FAL - Faux-Alabaster Acrylic
SOA - Satin Opal Acrylic
WAC - White Acrylic

Light Source

6L7 LTE - 43.2W/30K 6810 lumen LED 120-277V HPF
6L11 LTE - 68.4W/30K 9780 lumen LED
MB - Maximum 6x 150W A (by others)

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from [Luraline Palette](#)
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

2DIM010 LED 4-wire 0-10V Dimming - 120-277V
BBL 90 minutes Battery Backup - For LED only (100- 277V/50-60Hz Input Voltage)
SSP 10KV 120-277V Supplemental Surge Protection