



**Decorative ABS30** H: 9 W: 30 OAL: 35.50

### Description

Stem-hung 30" Acrylic Bowl pendant

### Specifications

<b>Housing</b>	Mixed metals		
<b>Diffuser/Optics</b>	<ul style="list-style-type: none"> <li>• FAL - Faux-Alabaster Acrylic</li> <li>• SOA - Satin Opal Acrylic</li> <li>• WAC - White Acrylic</li> </ul>		
<b>Light Source</b>	GUL	LTE	Medium Base
<b>Max Watts</b>	15.5 X 4	11.4 X 4	150 X 4
<b>Electrical</b>	<b>MB</b> - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. <b>GUL</b> - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver. <b>LTE</b> - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.		
<b>Mounting</b>	Mounts over 4" recessed outlet box.		
<b>Certification</b>	Manufactured in accordance with U.L. standard 1598 - For dry locations only		



**Ordering Guide:** Choose from each category, using designated code to specify.

ABS30					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

#### Diffuser/Optics

**FAL** - Faux-Alabaster Acrylic  
**SOA** - Satin Opal Acrylic  
**WAC** - White Acrylic

#### Light Source

**4L11 LTE** - 45.6W/30K 6520 Lm LED  
**4GUL15.5 A21** - 62W/27K 6400 Lm GU24 OmniLED  
**MB** - Maximum 4x150W A (by others)

#### Finish

**Standard**  
**BL** - Black  
**DB** - Dura-Bronze  
**WH** - White  
**Upgraded\***  
**RAL** - Specify Color #  
**UPG** - Select Color from Luraline Palette  
**Premium\***  
**CCM** - Custom Color  
**CIC** - Inner Color  
**CTC** - Clear Top Coat  
 \* Subject to Surcharge

#### Extras (Order Separately)

**SSP 120** 4KV 120V MOV1 Surge Suppressor