


Project:

Fixture Type:





Decorative ABS36 H: 11 W: 36 OAL: 35

Description

Stem-hung 36" Acrylic Bowl pendant

Specifications

Housing Mixed metals

Diffuser/Optics • FAL - Faux-Alabaster Acrylic

• SOA - Satin Opal Acrylic • WAC - White Acrylic

Light Source LTE Medium Base Max Watts 7.2 X 6 150 X 6

Electrical - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.

- Includes 50,000 Hr. LED light engine with 120-277V constant current driver.

Mounting Mounts over 4" recessed outlet box.

Certification Manufactured in accordance with U.L. standard 1598 - For dry locations only



Urc	lering (Guide:	Choose from	each	category,	using	designated	code	to	specify	у.
-----	----------	--------	-------------	------	-----------	-------	------------	------	----	---------	----

ABS36

MODEL **DIFFUSER** LIGHT SOURCE

Diffuser/Optics

FAL - Faux-Alabaster Acrylic **SOA** - Satin Opal Acrylic **WAC** - White Acrylic

Light Source

6L7 LTE - 43.2W/30K 6810 lumen LED 120-277V HPF MB - Maximum 6x 150W A (by others)

Standard

Finish

EXTRAS

BL - Black **DB** - Dura-Bronze WH - White Upgraded*

RAL - Specify Color # UPG - Select Color from Luraline Pallette

Premium*

CCM - Custom Color CIC - Inner Color CTC - Clear Top Coat * Subject to Surcharge Extras (Order Separately)

SSP 120 4KV 120V MOV1 Surge Suppressor



FINISH