



RLM CD 14 CORDX H: 12.75 W: 14 OAL: 51.75

Description

Parabolic dome pendant with 36" Black 18-3 cord. (White cord supplied with white fixtures)

Specifications

- Housing** Spun aluminum shade with stamped steel canopy*
- Diffuser/Optics** Lensed LED (no diffuser) for Dry locations only
- Light Source** LED
- Max Watts** 16.41
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - For dry locations only



Ordering Guide: Choose from each category, using designated code to specify.

CD 14 CORDX					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

LOZ - Lensed LED (no diffuser)

Light Source

- TL3 HO** - 3.04W/40K 982 Lm, 0-10V dimmable
- TL3** - 3.11W/30K 603 Lm, 0-10V dimmable
- TL5 HO** - 4.59W/40K 1287 Lm, 120V dimmable
- TL6 HO** - 6.16W/40K 1588 Lm, 120V dimmable
- TL6** - 6.32W/30K 1208 Lm, 120V dimmable
- TL8 HO** - 7.75W/40K 1886 Lm, 120V dimmable
- TL8** - 7.96W/30K 1502 Lm, 120V dimmable
- TL9 HO** - 9.36W/40K 2179 Lm, 120V dimmable
- TL10** - 9.62W/30K 1790 Lm, 120V dimmable
- TL11** - 11.3W/30K 2075 Lm, 120V dimmable
- TL14 HO** - 14.28W/40K 3040 Lm, 120V dimmable
- TL15** - 14.69W/30K 2626 Lm, 120V dimmable
- TL16 HO** - 15.94W/40K 3320 Lm, 120V dimmable
- TL16** - 16.41W/30K 2895 Lm, 120V dimmable

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from [Luraline Palette](#)
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 27K** Non-Stock item - consult factory for availability
- 35K** Neutral White
- DIM010** 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP** 10KV 120-277V Supplemental Surge Protection

NOTES:

- *Driver is housed in extended aluminum canopy (not shown)
- *Driver is housed in extended aluminum canopy (not shown)
- *Driver is housed in extended aluminum canopy (not shown)
- *Driver is housed in extended aluminum canopy (not shown)