



**Decorative CP16 CORD** H: 18.75 W: 16.38 OAL: 55.5

**Description**

Prismatic reflexor pendant with 36" Black 18-3 cord. (White cord supplied with white fixtures)

**Specifications**

**Housing** Spun aluminum bullet with stamped steel canopy

**Diffuser/Optics** Bare lamp (no diffuser) for Dry locations only

|                     |     |     |             |
|---------------------|-----|-----|-------------|
| <b>Light Source</b> | GUL | MBL | Medium Base |
| <b>Max Watts</b>    | 15  | 18  | 200         |

**Electrical**

- MB** - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
- MBL** - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.
- GUL** - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.

**Mounting** Mounts over 4" recessed outlet box.

**Certification** Manufactured in accordance with U.L. standard 1598 - For dry locations only



**Ordering Guide:** Choose from each category, using designated code to specify.

|           |          |              |        |        |  |
|-----------|----------|--------------|--------|--------|--|
| CP16 CORD |          |              |        |        |  |
| MODEL     | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS |  |

**Diffuser/Optics**

Bare-lamp (no diffuser)

**Light Source**

- MBL9.8A** - 9.8W/30K 800 Lm OmniLED
- MBL10A JAB** - 10W/30K 800 Lm 90+ CRI OmniLED
- MBL11A** - 11W/30K 1100 Lm OmniLED
- GUL11A** - 11W/27K 1100 Lm GU24 OmniLED
- GUL15A** - 15W/27K 1600 Lm GU24 OmniLED
- MBL15A** - 15./30K 1600 Lm OmniLED
- MBL18A JAB** - 18W/30K 1600 Lm 90+ CRI OmniLED
- MB** - Maximum 200W A (by others)

**Finish**

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded\***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium\***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**

- DWG16** 16" Wire Guard
- SSP 120** 4KV 120V MOV1 Surge Suppressor

NOTES: DWG Wire Guard may NOT be used in combination with CDL diffuser.  
 DWG Wire Guard may NOT be used in combination with CDL diffuser.  
 DWG Wire Guard may NOT be used in combination with CDL diffuser.  
 DWG Wire Guard may NOT be used in combination with CDL diffuser.