



Helos GPC 900X H: 9.50 W: 9 OAL: 48

Description

Helos/Genera pendant with 36" Black 18-3 cord. (White cord supplied with white fixtures)

Specifications

Housing Heavy-wall spun aluminum with cast fitter and stamped steel canopy*

Diffuser/Optics

- Clear tempered glass cylinder
- Frosted glass cylinder

Light Source LED

Max Watts 9.62

Electrical TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).

Mounting Mounts over 4" recessed outlet box.

Certification Manufactured in accordance with U.L. standard 1598 - For dry locations only



Ordering Guide: Choose from each category, using designated code to specify.

GPC 900X				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

CL - Clear glass
FR - Frosted glass

Light Source

TL3 HO - 3.04W/40K 982 Lm, 0-10V dimmable
TL3 - 3.11W/30K 603 Lm, 0-10V dimmable
TL5 HO - 4.59W/40K 1287 Lm, 120V dimmable
TL5 - 4.7W/30K 909 Lm, 120V dimmable
TL6 HO - 6.16W/40K 1588 Lm, 120V dimmable
TL6 - 6.32W/30K 1208 Lm, 120V dimmable
TL8 HO - 7.75W/40K 1886 Lm, 120V dimmable
TL8 - 7.96W/30K 1502 Lm, 120V dimmable
TL9 HO - 9.36W/40K 2179 Lm, 120V dimmable
TL10 - 9.62W/30K 1790 Lm, 120V dimmable

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
* Subject to Surcharge

Extras (Order Separately)

27K Non-Stock item - consult factory for availability
35K Neutral White
DIM010 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
SSP 10KV 120-277V Supplemental Surge Protection

NOTES:

- *Driver is housed in extended aluminum canopy (not shown)
- *Driver is housed in extended aluminum canopy (not shown)
- *Driver is housed in extended aluminum canopy (not shown)
- *Driver is housed in extended aluminum canopy (not shown)
- *Driver is housed in extended aluminum canopy (not shown)
- *Driver is housed in extended aluminum canopy (not shown)