



Helos GPS 900 H: 9.50 W: 9 OAL: 23.25

Description

Helos/Genera with 12" stem and 40° swivel canopy

Specifications

Housing	Heavy-wall spun aluminum with cast fitter, extruded stem and stamped steel canopy	
Diffuser/Optics	<ul style="list-style-type: none"> • Clear tempered glass cylinder • Frosted glass cylinder 	
Light Source	MBL	Medium Base
Max Watts	13	100
Electrical	MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. MBL - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.	
Mounting	Mounts over 4" recessed outlet box.	
Certification	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations	



Ordering Guide: Choose from each category, using designated code to specify.

GPS 900					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

- CL - Clear glass
- FR - Frosted glass

Light Source

- MB25 A** - 25W MAX. MED base (A19 lamp by others)
- MBL6A** - 5.5W/30K 470 Lm OmniLED
- MBL9.8A** - 9.8W/30K 800 Lm OmniLED
- MBL10A JAS** - 10W/30K 800 Lm 90+ CRI OmniLED
- MBL13A JAS** - 13W/30K 1100 Lm 90+ CRI OmniLED
- MB** - 100W Max Incand A (by others)

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from [Luraline Palette](#)
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- SSP 120** 4KV 120V MOV1 Surge Suppressor