



Helos GWM 1400 H: 9.50 W: 14 E: 18 MC: 3

Description

9" Tapered shade, straight arm

Specifications

- Housing** Heavy-wall spun aluminum with cast fitter/canopy and extruded arm
- Diffuser/Optics**
- Clear tempered glass cylinder
 - Frosted glass cylinder
- Light Source** GUL MBL Medium Base
- Max Watts** 11 13 100
- Electrical**
- MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
 - MBL - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.
 - GUL - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.
- Mounting** Mounts over 4" recessed outlet box
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations



Ordering Guide: Choose from each category, using designated code to specify.

GWM 1400				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

- CL - Clear glass
- FR - Frosted glass

Light Source

- MB25 A - 25W MAX. MED base (A19 lamp by others)
- MBL6A - 5.5W/30K 470 Lm OmniLED
- MBL9.8A - 9.8W/30K 800 Lm OmniLED
- GUL9.8A - 9.8W/27K 800 Lm GU24 OmniLED
- MBL10A JAB - 10W/30K 800 Lm 90+ CRI OmniLED
- GUL11A - 11W/27K 1100 Lm GU24 OmniLED
- MBL11A - 11W/30K 1100 Lm OmniLED
- MBL13A JAB - 13W/30K 1100 Lm 90+ CRI OmniLED
- MB - 100W Max Incand A (by others)

Finish

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded***
- RAL - Specify Color #
- UPG - Select Color from Luraline Palette
- Premium***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)