



## Helos HL301 CORD H: 11 W: 10 OAL: 47

### Description

10" Disk Helos pendant with 36" Black 18-3 cord. (White cord supplied with white fixtures)

### Specifications

<b>Housing</b>	Heavy-wall spun aluminum with cast fitter and stamped steel canopy	
<b>Diffuser/Optics</b>	<ul style="list-style-type: none"> <li>• Clear tempered glass cylinder</li> <li>• Frosted Glass cylinder</li> </ul>	
<b>Light Source</b>	MBL	Medium Base
<b>Max Watts</b>	13	100
<b>Electrical</b>	<b>MB</b> - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. <b>MBL</b> - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.	
<b>Mounting</b>	Mounts over 4" recessed outlet box.	
<b>Certification</b>	Manufactured in accordance with U.L. standard 1598 - For dry locations only	



**Ordering Guide:** Choose from each category, using designated code to specify.

HL301 CORD					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

#### Diffuser/Optics

**CL** - Clear glass  
**FR** - Frosted glass

#### Light Source

**MB25 A** - 25W MAX. MED base (A19 lamp by others)  
**MBL6A** - 5.5W/30K 470 Lm OmniLED  
**MBL9.8A** - 9.8W/30K 800 Lm OmniLED  
**MBL10A JA8** - 10W/30K 800 Lm 90+ CRI OmniLED  
**MBL13A JA8** - 13W/30K 1100 Lm 90+ CRI OmniLED  
**MB** - 100W Max Incand A (by others)

#### Finish

**Standard**  
**BL** - Black  
**DB** - Dura-Bronze  
**WH** - White  
**Upgraded\***  
**RAL** - Specify Color #  
**UPG** - Select Color from Luraline Palette  
**Premium\***  
**CCM** - Custom Color  
**CIC** - Inner Color  
**CTC** - Clear Top Coat  
 \* Subject to Surcharge

#### Extras (Order Separately)

**SSP 120** 4KV 120V MOV1 Surge Suppressor