



**Helos HL301 LWMX** H: 18 W: 10 E: 21 MC: 3

**Description**

10" Disk, L-arm

**Specifications**

- Housing** Heavy-wall spun aluminum with cast fitter/canopy\* and extruded arm
- Diffuser/Optics**
  - Clear tempered glass cylinder
  - Frosted Glass cylinder
- Light Source** LED
- Max Watts** 9.62
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations



**Ordering Guide:** Choose from each category, using designated code to specify.

HL301 LWMX				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**

- CL - Clear glass
- FR - Frosted glass

**Light Source**

- TL3 HO - 3.04W/40K 982 Lm, 0-10V dimmable
- TL3 - 3.11W/30K 603 Lm, 0-10V dimmable
- TL5 HO - 4.59W/40K 1287 Lm, 120V dimmable
- TL5 - 4.7W/30K 909 Lm, 120V dimmable
- TL6 HO - 6.16W/40K 1588 Lm, 120V dimmable
- TL6 - 6.32W/30K 1208 Lm, 120V dimmable
- TL8 HO - 7.75W/40K 1886 Lm, 120V dimmable
- TL8 - 7.96W/30K 1502 Lm, 120V dimmable
- TL9 HO - 9.36W/40K 2179 Lm, 120V dimmable
- TL10 - 9.62W/30K 1790 Lm, 120V dimmable

**Finish**

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded\***
- RAL - Specify Color #
- UPG - Select Color from Luraline Palette
- Premium\***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**

- 27K Non-Stock item - consult factory for availability
- 35K Neutral White
- DIM010 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP 10KV 120-277V Supplemental Surge Protection