



### Helos HL301 STEM H: 10 W: 10 OAL: 23.50

#### Description

10" Disk pendant with 12" stem and 40° swivel canopy

#### Specifications

<b>Housing</b>	Heavy-wall spun aluminum with cast fitter, extruded stem and stamped steel canopy		
<b>Diffuser/Optics</b>	<ul style="list-style-type: none"> <li>• Clear tempered glass cylinder</li> <li>• Frosted Glass cylinder</li> </ul>		
<b>Light Source</b>	GUL	MBL	Medium Base
<b>Max Watts</b>	11	13	100
<b>Electrical</b>	<b>MB</b> - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. <b>MBL</b> - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures. <b>GUL</b> - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.		
<b>Mounting</b>	Mounts over 4" recessed outlet box.		
<b>Certification</b>	Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations		



#### Ordering Guide: Choose from each category, using designated code to specify.

HL301 STEM					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

#### Diffuser/Optics

- CL - Clear glass
- FR - Frosted glass

#### Light Source

- MB25 A** - 25W MAX. MED base (A19 lamp by others)
- MBL6A** - 5.5W/30K 470 Lm OmniLED
- MBL9.8A** - 9.8W/30K 800 Lm OmniLED
- GUL9.8A** - 9.8W/27K 800 Lm GU24 OmniLED
- MBL10A JAB** - 10W/30K 800 Lm 90+ CRI OmniLED
- GUL11A** - 11W/27K 1100 Lm GU24 OmniLED
- MBL11A** - 11W/30K 1100 Lm OmniLED
- MBL13A JAB** - 13W/30K 1100 Lm 90+ CRI OmniLED
- MB** - 100W Max Incand A (by others)

#### Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded\***
- RAL** - Specify Color #
- UPG** - Select Color from [Luraline Palette](#)
- Premium\***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- \* Subject to Surcharge

#### Extras (Order Separately)

- SSP 120** 4KV 120V MOV1 Surge Suppressor