


Project: _____

Fixture Type: _____



Helos HL301XL STEMX H: 12 W: 18 OAL: 28

Description

18" Disk pendant with 12" stem and 40° swivel canopy

Specifications

- Housing** Heavy-wall spun aluminum with cast fitter, extruded stem and stamped steel canopy*
- Diffuser/Optics**
 - Clear tempered glass cylinder
 - Frosted glass cylinder
- Light Source** LED
- Max Watts** 14.69
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations



Ordering Guide: Choose from each category, using designated code to specify.

<u>HL301XL STEMX</u>					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

- CL - Clear glass
- FR - Frosted glass

Light Source

- TL11 HO - 10.99W/40K 2470 Lm, 120V dimmable
- TL11 - 11.3W/30K 2075 Lm, 120V dimmable
- TL13 HO - 12.62W/40K 2756 Lm, 120V dimmable
- TL13 - 12.99W/30K 2352 Lm, 120V dimmable
- TL14 HO - 14.28W/40K 3040 Lm, 120V dimmable
- TL15 - 14.69W/30K 2626 Lm, 120V dimmable

Finish

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded***
- RAL - Specify Color #
- UPG - Select Color from Luraline Palette

Premium*

- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 27K Non-Stock item - consult factory for availability
- 35K Neutral White
- DIM010 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP 10KV 120-277V Supplemental Surge Protection

NOTES: *Driver is housed in extended aluminum canopy (not shown)
 *Driver is housed in extended aluminum canopy (not shown)
 *Driver is housed in extended aluminum canopy (not shown)
 *Driver is housed in extended aluminum canopy (not shown)
 *Driver is housed in extended aluminum canopy (not shown)