



**Helos HL301XL WMX** H: 14 W: 18 E: 26 MC: 4.75

**Description**

18" Disk, Arm-mount

**Specifications**

- Housing** Heavy-wall spun aluminum with cast fitter/canopy and extruded arm
- Diffuser/Optics**
  - Clear tempered glass cylinder
  - Frosted Glass cylinder
- Light Source** LED
- Max Watts** 14.69
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - - Suitable for wet locations

**Ordering Guide:** Choose from each category, using designated code to specify.

HL301XL WMX				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**

- CL - Clear glass
- FR - Frosted glass

**Light Source**

- TL11 HO - 10.99W/40K 2470 Lm, 120V dimmable
- TL11 - 11.3W/30K 2075 Lm, 120V dimmable
- TL13 HO - 12.62W/40K 2756 Lm, 120V dimmable
- TL13 - 12.99W/30K 2352 Lm, 120V dimmable
- TL14 HO - 14.28W/40K 3040 Lm, 120V dimmable
- TL15 - 14.69W/30K 2626 Lm, 120V dimmable

**Finish**

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded\***
- RAL - Specify Color #
- UPG - Select Color from [Luraline Palette](#)
- Premium\***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**

- 27K Non-Stock item - consult factory for availability
- 35K Neutral White
- DIM010 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP 10KV 120-277V Supplemental Surge Protection

NOTES: \*Driver is housed in extended aluminum canopy (not shown)