



Helos HL302 UWMX H: 19 W: 14 E: 23 MC: 14.25

Description

14" Tapered, U-arm

Specifications

| | |
|------------------------|---|
| Housing | Heavy-wall spun aluminum with cast fitter/canopy* and extruded arm |
| Diffuser/Optics | <ul style="list-style-type: none"> • Clear tempered glass cylinder • Frosted glass cylinder |
| Light Source | LED |
| Max Watts | 9.62 |
| Electrical | TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent). |
| Mounting | Mounts over 4" recessed outlet box. |
| Certification | Manufactured in accordance with U.L. standard 1598 Suitable for damp or dry locations - Suitable for wet locations |

Ordering Guide: Choose from each category, using designated code to specify.

| | | | | | |
|------------|----------|--------------|--------|--------|--|
| HL302 UWMX | | | | | |
| MODEL | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS | |

Diffuser/Optics

- CL - Clear glass
- FR - Frosted glass

Light Source

- TL3 HO - 3.04W/40K 982 Lm, 0-10V dimmable
- TL3 - 3.11W/30K 603 Lm, 0-10V dimmable
- TL5 HO - 4.59W/40K 1287 Lm, 120V dimmable
- TL5 - 4.7W/30K 909 Lm, 120V dimmable
- TL6 HO - 6.16W/40K 1588 Lm, 120V dimmable
- TL6 - 6.32W/30K 1208 Lm, 120V dimmable
- TL8 HO - 7.75W/40K 1886 Lm, 120V dimmable
- TL8 - 7.96W/30K 1502 Lm, 120V dimmable
- TL9 HO - 9.36W/40K 2179 Lm, 120V dimmable
- TL10 - 9.62W/30K 1790 Lm, 120V dimmable

Finish

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded***
- RAL - Specify Color #
- UPG - Select Color from Luraline Palette
- Premium***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 27K Non-Stock item - consult factory for availability
- 35K Neutral White
- DIM010 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP 10KV 120-277V Supplemental Surge Protection