



Helos HL302XL PR H: 30.50 W: 22 E: 34.50

Description

22" Tapered, U-arm postlight (slips 4")

Specifications

Housing	Heavy-wall spun aluminum with cast fitter and extruded arm		
Diffuser/Optics	<ul style="list-style-type: none"> • Clear prismatic glass cylinder • Clear tempered glass cylinder • Frosted Glass cylinder 		
Light Source	GUL	MBL	Medium Base
Max Watts	15	18	200
Electrical	<p>MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.</p> <p>MBL - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.</p> <p>GUL - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.</p>		
Mounting	Slips 4" OD (PR Series) poles - order separately		
Certification	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations		



Ordering Guide: Choose from each category, using designated code to specify.

HL302XL PR				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

- CL** - Clear glass
- CPR** - Clear prismatic glass
- FR** - Frosted glass

Light Source

- MB25 A** - 25W MAX. MED base (A19 lamp by others)
- GUL9.8A** - 9.8W/27K 800 Lm GU24 OmniLED
- MBL11A** - 11W/30K 1100 Lm OmniLED
- GUL11A** - 11W/27K 1100 Lm GU24 OmniLED
- MBL13A JAB** - 13W/30K 1100 Lm 90+ CRI OmniLED
- MBL15A** - 15./30K 1600 Lm OmniLED
- GUL15A** - 15W/27K 1600 Lm GU24 OmniLED
- MBL18A JAB** - 18W/30K 1600 Lm 90+ CRI OmniLED
- MB** - Maximum 200W A (by others)

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)