



**Helos HL302XL PR2** H: 30.50 W: 22 E: 65.50

**Description**

22" Tapered, Double U-arm postlight (slips 4")

**Specifications**

<b>Housing</b>	Heavy-wall spun aluminum with cast fitter and extruded arm			
<b>Diffuser/Optics</b>	<ul style="list-style-type: none"> <li>• Clear prismatic glass cylinder</li> <li>• Clear tempered glass cylinder</li> <li>• Frosted Glass cylinder</li> </ul>			
<b>Light Source</b>	MBL	GUL	MBL	Medium Base
<b>Max Watts</b>	11	15 X 2	25 X 2	200 X 2
<b>Electrical</b>	<p><b>MB</b> - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.</p> <p><b>MBL</b> - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.</p> <p><b>GUL</b> - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.</p>			
<b>Mounting</b>	Slips 4" OD (PR Series) poles - order separately			
<b>Certification</b>	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations			



**Ordering Guide:** Choose from each category, using designated code to specify.

HL302XL PR2				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**

- CL** - Clear glass
- CPR** - Clear prismatic glass
- FR** - Frosted glass

**Light Source**

- 2MBL6A** - 11W/30K 940 Lm OmniLED
- 2GUL9.8A** - 19.6W/27K 1600 Lm GU24 OmniLED
- MBL11A** - 11W/30K 1100 Lm OmniLED
- 2GUL11A** - 22W/27K 2200 Lm GU24 OmniLED
- 2MBL15A** - 30W/30K 3200 Lm OmniLED
- 2GUL15A** - 30W/27K 3200 Lm GU24 OmniLED
- 2MB25A** - 2x 25W MAX. MED base (lamp by others)
- MB** - Maximum 2x 200W A (by others)

**Finish**

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded\***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium\***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**