



Helos HL302XL STEM H: 15.75 W: 22 OAL: 29.50

Description

22" Tapered pendant with 12" stem and 40° swivel canopy

Specifications

- Housing** Heavy-wall spun aluminum with cast fitter, extruded stem and stamped steel canopy
- Diffuser/Optics**
 - Clear tempered glass cylinder
 - Frosted glass cylinder
- Light Source**

GUL	MBL	Medium Base
-----	-----	-------------
- Max Watts**

15	18	150
----	----	-----
- Electrical**
 - MB** - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
 - MBL** - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.
 - GUL** - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 Suitable for damp or dry locations - Suitable for wet locations



Ordering Guide: Choose from each category, using designated code to specify.

HL302XL STEM

MODEL DIFFUSER LIGHT SOURCE FINISH EXTRAS

Diffuser/Optics

- CL** - Clear glass
- FR** - Frosted glass

Light Source

- MB25 A** - 25W MAX. MED base (A19 lamp by others)
- GUL15A** - 15W/27K 1600 Lm GU24 OmniLED
- MBL15A** - 15./30K 1600 Lm OmniLED
- MBL18A JA8** - 18W/30K 1600 Lm 90+ CRI OmniLED
- MB** - 150W Max Incand A (by others)

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- SSP 120** 4KV 120V MOV1 Surge Suppressor