



**Helos HL302XL STEMX** H: 15.75 W: 22 OAL: 31

**Description**

22" Tapered pendant with 12" stem and 40° swivel canopy

**Specifications**

<b>Housing</b>	Spun aluminum with extruded stem and stamped steel canopy*
<b>Diffuser/Optics</b>	<ul style="list-style-type: none"> <li>• Clear tempered glass cylinder</li> <li>• Frosted glass cylinder</li> </ul>
<b>Light Source</b>	LED
<b>Max Watts</b>	14.69
<b>Electrical</b>	TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
<b>Mounting</b>	Mounts over 4" recessed outlet box.
<b>Certification</b>	Manufactured in accordance with U.L. standard 1598 - For dry locations only

**Ordering Guide:** Choose from each category, using designated code to specify.

HL302XL STEMX				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**

- CL - Clear glass
- FR - Frosted glass

**Light Source**

- TL11 HO - 10.99W/40K 2470 Lm, 120V dimmable
- TL11 - 11.3W/30K 2075 Lm, 120V dimmable
- TL13 HO - 12.62W/40K 2756 Lm, 120V dimmable
- TL13 - 12.99W/30K 2352 Lm, 120V dimmable
- TL14 HO - 14.28W/40K 3040 Lm, 120V dimmable
- TL15 - 14.69W/30K 2626 Lm, 120V dimmable

**Finish**

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded\***
- RAL - Specify Color #
- UPG - Select Color from Luraline Palette
- Premium\***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**

- 27K** Non-Stock item - consult factory for availability
- 35K** Neutral White
- DIM010** 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP** 10KV 120-277V Supplemental Surge Protection

NOTES:  
\*Driver is housed in extended aluminum canopy (not shown)