



Helos HL302XL WM H: 15.75 W: 22 E: 28 MC: 4.75

Description

22" Tapered shade, straight arm

Specifications

Housing	Heavy-wall spun aluminum with cast fitter/canopy and extruded arm		
Diffuser/Optics	<ul style="list-style-type: none"> • Clear tempered glass cylinder • Frosted Glass cylinder 		
Light Source	GUL	MBL	Medium Base
Max Watts	15	18	200
Mounting	Mounts over 4" recessed outlet box.		
Certification	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations		



Ordering Guide: Choose from each category, using designated code to specify.

HL302XL WM					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

CL - Clear glass
FR - Frosted glass

Light Source

MB25 A - 25W MAX. MED base (A19 lamp by others)
MBL13A JA8 - 13W/30K 1100 Lm 90+ CRI OmniLED
GUL15A - 15W/27K 1600 Lm GU24 OmniLED
MBL18A JA8 - 18W/30K 1600 Lm 90+ CRI OmniLED
MB - Maximum 200W A (by others)

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
* Subject to Surcharge

Extras (Order Separately)

27K Non-Stock item - consult factory for availability
35K Neutral White
50K Daylight (Non-Stock item - consult factory for availability)
DIM010 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
SSP 10KV 120-277V Supplemental Surge Protection