



Helos HL302XLX PR H: 30.50 W: 22 E: 34.50

Description

22" Tapered, U-arm postlight (slips 4")

Specifications

Housing	Heavy-wall spun aluminum with cast fitter and extruded arm
Diffuser/Optics	<ul style="list-style-type: none"> • Clear prismatic glass cylinder • Clear tempered glass cylinder • Frosted Glass cylinder
Light Source	LED
Max Watts	14.69
Electrical	TL/HO- L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
Mounting	Slips 4" OD (PR Series) poles - order separately
Certification	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations

Ordering Guide: Choose from each category, using designated code to specify.

HL302XLX PR					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

- CL - Clear glass
- CPR - Clear prismatic glass
- FR - Frosted glass

Light Source

- TL11 HO - 10.99W/40K 2470 Lm, 120V dimmable
- TL11 - 11.3W/30K 2075 Lm, 120V dimmable
- TL13 HO - 12.62W/40K 2756 Lm, 120V dimmable
- TL13 - 12.99W/30K 2352 Lm, 120V dimmable
- TL14 HO - 14.28W/40K 3040 Lm, 120V dimmable
- TL15 - 14.69W/30K 2626 Lm, 120V dimmable

Finish

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded***
- RAL - Specify Color #
- UPG - Select Color from Luraline Palette
- Premium***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 27K Non-Stock item - consult factory for availability
- 35K Neutral White
- DIM010 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP 10KV 120-277V Supplemental Surge Protection