



Helos HL302XLX PR2 H: 30.50 W: 22 E: 65.50

Description

22" Tapered, Double U-arm postlight (slips 4")

Specifications

- Housing** Heavy-wall spun aluminum with cast fitter and extruded arm
- Diffuser/Optics**
 - Clear prismatic glass cylinder
 - Clear tempered glass cylinder
 - Frosted Glass cylinder
- Light Source** LED
- Max Watts** 14.89 X 2
- Electrical** TL/HO- L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Slips 4" OD (PR Series) poles - order separately
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations

Ordering Guide: Choose from each category, using designated code to specify.

HL302XLX PR2				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

- CL - Clear glass
- CPR - Clear prismatic glass
- FR - Frosted glass

Light Source

- 2TL11 HO - 21.98W/40K 4970 Lm, 120V dimmable
- 2TL11 - 22.6W/30K 4150 Lm, 120V dimmable
- 2TL13 HO - 25.32W/40K 5512 Lm, 120V dimmable
- 2TL13 - 25.98W/30K 4704 Lm, 120V dimmable
- 2TL14 HO - 28.56W/40K 6080 Lm, 120V dimmable
- 2TL15 - 29.78W/30K 5252 Lm, 120V dimmable

Finish

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded***
- RAL - Specify Color #
- UPG - Select Color from Luraline Palette
- Premium***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 27K Non-Stock item - consult factory for availability
- 2DIM010 LED 4-wire 0-10V Dimming - 120-277V
- 35K Neutral White
- SSP 10KV 120-277V Supplemental Surge Protection