



**Helos HL302X P2** H: 19 W: 14 E: 41

**Description**

14" Tapered, Double U-arm postlight (slips 3")

**Specifications**

- Housing** Heavy-wall spun aluminum with cast fitter and extruded arm
- Diffuser/Optics**
  - Clear prismatic glass cylinder
  - Clear tempered glass cylinder
  - Frosted Glass cylinder
- Light Source** LED
- Max Watts** 9.62 X 2
- Electrical** TL/HO- L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Slips 3" OD (PX Series) poles - order separately
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations

**Ordering Guide:** Choose from each category, using designated code to specify.

HL302X P2				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**

- CL - Clear glass
- CPR - Clear prismatic glass
- FR - Frosted glass

**Light Source**

- 2TL3 HO - 6.08W/40K 1964 Lm, 0-10V dimmable
- 2TL5 HO - 9.2W/40K 2408 Lm, 120V dimmable
- 2TL5 - 9.4W/30K 1708 Lm, 120V dimmable
- 2TL6 HO - 12.32W/40K 3176 Lm, 120V dimmable
- 2TL6/P - 12.64W/30K 2416 Lm, 120V dimmable
- 2TL6 - 12.64W/30K 2416 Lm, 120V dimmable
- 2TL8 HO - 15.5W/40K 3772 Lm, 120V dimmable
- 2TL8 - 15.92W/30K 2822 Lm, 120V dimmable
- 2TL9 HO - 18.72W/40K 4358 Lm, 120V dimmable
- 2TL10 - 19.24W/30K 3580 Lm, 120V dimmable

**Finish**

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded\***
- RAL - Specify Color #
- UPG - Select Color from Luraline Palette
- Premium\***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**

- 27K Non-Stock item - consult factory for availability
- 2DIM010 LED 4-wire 0-10V Dimming - 120-277V
- 35K Neutral White
- SSP 10KV 120-277V Supplemental Surge Protection