



Helos HL317 RD H: 21 W: 18 E: 12.75 MC: 10.50

Description

Helos Sconce with Rain Deflector

Specifications

- Housing** Heavy Wall and cast alloys with spun aluminum reflectors.
- Diffuser/Optics**
- Clear tempered glass cylinder
 - Frosted Glass cylinder
- Light Source** GUL MBL Medium Base
- Max Watts** 11 X 2 110 X 2 100 X 2
- Electrical**
- MB** - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
 - MBL** - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.
 - GUL** - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.
- Mounting** Mounts over 4" recessed outlet box
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations



Ordering Guide: Choose from each category, using designated code to specify.

HL317 RD				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

- CL** - Clear glass
- FR** - Frosted glass

Light Source

- 2MBL9.8A** - 19.6W/30K 1600 Lm OmniLED
- 2GUL9.8A** - 19.6W/27K 1600 Lm GU24 OmniLED
- 2GUL11A** - 22W/27K 2200 Lm GU24 OmniLED
- MB** - Maximum 2x 100W A (by others)
- 2MBL11A** - 23W/30K 2280 Lm OmniLED

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- SSP 120** 4KV 120V MOV1 Surge Suppressor