



**Helos HL333** H: 8.75 W: 10

**Description**

10" Disk, Helos surface-mounted

**Specifications**

<b>Housing</b>	Heavy wall spun aluminum with cast fitter	
<b>Diffuser/Optics</b>	<ul style="list-style-type: none"> <li>• Clear prismatic glass cylinder</li> <li>• Clear tempered glass cylinder</li> <li>• Frosted Glass cylinder</li> </ul>	
<b>Light Source</b>	MBL	Medium Base
<b>Max Watts</b>	13	100
<b>Electrical</b>	<b>MB</b> - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. <b>MBL</b> - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.	
<b>Mounting</b>	Mounts over 4" recessed outlet box.	
<b>Certification</b>	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations	

**Ordering Guide:** Choose from each category, using designated code to specify.

HL333					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

**Diffuser/Optics**

- CL - Clear glass
- CPR - Clear prismatic glass
- FR - Frosted glass

**Light Source**

- MBL6A - 5.5W/30K 470 Lm OmniLED
- MBL9.8A - 9.8W/30K 800 Lm OmniLED
- MBL10A JAB - 10W/30K 800 Lm 90+ CRI OmniLED
- MBL13A JAB - 13W/30K 1100 Lm 90+ CRI OmniLED
- MB - 100W Max Incand A (by others)

**Finish**

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded\***
- RAL - Specify Color #
- UPG - Select Color from Luraline Palette
- Premium\***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**