



Helos HLD302XL WM H: 15.75 W: 22 E: 28 MC: 4.75

Description

22" Tapered shade downlight, straight arm

Specifications

- Housing** Spun aluminum shade with extruded arm and cast canopy
- Diffuser/Optics**
 - Lensed LED (no diffuser) for Dry locations only
 - TurboLED Extra wide beam silicone optic
 - TurboLED wide beam silicone optic
- Light Source** LED
- Max Watts** 36.12
- Electrical** TL/HO- L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 -



Ordering Guide: Choose from each category, using designated code to specify.

HLD302XL WM					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

- LOW** - Wide beam optic
- LOX** - Extra wide beam optic
- LOZ** - Lensed LED (no diffuser)

Light Source

- TL5 HO** - 4.59W/40K 1287 Lm, 120V dimmable
- TL11 HO** - 10.99W/40K 2470 Lm, 120V dimmable
- TL19 HO** - 19.3W/40K 3871 Lm, 120V dimmable
- TL20** - 19.9W/30K 3421 Lm, 0-10V dimmable
- TL23 HO** - 22.71W/40K 4410 Lm, 0-10V dimmable
- TL23** - 23.41W/30K 3931 Lm, 0-10V dimmable
- TL27** - 26.98W/30K 4428 Lm, 0-10V dimmable
- TL30 HO** - 29.65W/40K 5455 Lm, 0-10V dimmable
- TL31** - 30.6W/30K 4913 Lm, 0-10V dimmable
- TL35 HO** - 34.95W/40K 6213 Lm, 0-10V dimmable
- TL36** - 36.12W/30K 5620 Lm, 0-10V dimmable

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 27K** Non-Stock item - consult factory for availability
- 35K** Neutral White
- DIM010** 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP** 10KV 120-277V Supplemental Surge Protection