



Area/Bollard LBOFG3 H: 41.63 W: 7

Description

This is a round, bollard-style fixture with a flat-top design with Type III refractor. This is an extremely durable fixture, with extruded aluminum housing with flush-mounting base and vandal-resistant screws, black powdercoat finish over chromate conversion coating, internal ballast tray, and 50,000 estimated life. It delivers up to 2,089 lumens while using just 14.5 Watts. Standard applications for this Bollard-style design are walkways, parks, outdoor shopping areas, rural trails, and much more. CSA listed for wet locations.

Specifications

- Housing** Extruded aluminum with cast base
- Diffuser/Optics** Clear Polycarbonate
- Light Source** LTE
- Max Watts** 14.5
- Electrical** LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.
- Mounting** Mounting kit with 8" anchor bolts included
- Certification** Manufactured in accordance with U.L. standard 1598 - CSA Listed for Wet Locations



Ordering Guide: Choose from each category, using designated code to specify.

LBOFG3					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

Clear Polycarbonate Lens

Light Source

L15 LTE 50K - 14.5W/50K 2089 lumen LED

Finish

Standard
BT - Black (textured)
ZT - Bronze (textured)

Extras (Order Separately)

(D) FUSE DOUBLE FUSED
(S) FUSE SINGLE FUSED
BBL 90 minutes Battery Backup - For LED only (100- 277V/50-60Hz Input Voltage)
GS180 180° Glare Shield
SSP 10KV 120-277V Supplemental Surge Protection