



**Area/Bollard**    **LBOLSS**    H: 41.75 W: 7

### Description

The stainless-steel version of the most popular style of Bollard. It has a domed top design and louvers. Formed 316L stainless-steel housing with flush mounting base and vandal resistant screws makes this very easy to maintain. The 50,000 hours of estimated life makes it easy to live with. The high-efficiency LED yields 2,089 lumens while generating only 14.5 watts.

### Specifications

- Housing**            Extruded aluminum with cast base
- Diffuser/Optics**    Clear Polycarbonate
- Light Source**        LTE
- Max Watts**            14.5
- Electrical**            LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.
- Mounting**            Mounting kit with 8" anchor bolts included
- Certification**        Manufactured in accordance with U.L. standard 1598 - CSA Listed for Wet Locations



**Ordering Guide:** Choose from each category, using designated code to specify.

LBOLSS					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

**Diffuser/Optics**

Clear Polycarbonate Lens

**Light Source**

**L15 LTE 50K** - 14.5W/50K 2089 lumen LED

**Finish**

**Standard**

**Extras (Order Separately)**

- (D) FUSE** DOUBLE FUSED
- (S) FUSE** SINGLE FUSED
- BBL** 90 minutes Battery Backup - For LED only (100- 277V/50-60Hz Input Voltage)
- GS180** 180° Glare Shield
- SSP** 10KV 120-277V Supplemental Surge Protection