



**RLM RA11 GNL** H: 19 W: 10.50 E: 19 MC: 3

**Description**

11" Angled, 11" L-arm

**Specifications**

**Housing** Spun aluminum shade with extruded arm and cast

**Diffuser/Optics**

- Bare lamp (no diffuser) for Dry locations only
- Clear tempered glass cylinder
- Frosted glass cylinder

**Light Source** GUL MBL Medium Base

**Max Watts** 11 13 100

**Electrical**

- MB** - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
- MBL** - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.
- GUL** - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.

**Mounting** Mounts over 4" recessed outlet box.

**Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations (with diffuser only) -



**Ordering Guide:** Choose from each category, using designated code to specify.

RA11 GNL				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**

Bare-lamp (no diffuser)  
**CL** - Clear glass  
**FR** - Frosted Glass

**Light Source**

**MB25 A** - 25W MAX. MED base (A19 lamp by others)  
**MBL6A** - 5.5W/30K 470 Lm OmniLED  
**MBL9.8A** - 9.8W/30K 800 Lm OmniLED  
**MBL10A JAB** - 10W/30K 800 Lm 90+ CRI OmniLED  
**MBL11A** - 11W/30K 1100 Lm OmniLED  
**GUL11A** - 11W/27K 1100 Lm GU24 OmniLED  
**MBL11A** - 11W/30K 1100 Lm OmniLED  
**MBL13A JAB** - 13W/30K 1100 Lm 90+ CRI OmniLED  
**MB** - 100W Max Incand A (by others)

**Finish**

**Standard**  
**BL** - Black  
**DB** - Dura-Bronze  
**WH** - White  
**Upgraded\***  
**RAL** - Specify Color #  
**UPG** - Select Color from Luraline Palette  
**Premium\***  
**CCM** - Custom Color  
**CIC** - Inner Color  
**CTC** - Clear Top Coat  
 \* Subject to Surcharge

**Extras (Order Separately)**

**CG3** Cast aluminum guard (requires diffuser)  
**SSP 120** 4KV 120V MOV1 Surge Suppressor