



RLM RA11 GNLX H: 19 W: 10.5 E: 21 MC: 3

Description

11" Angled, 11" L-arm

Specifications

- Housing** Spun aluminum shade with extruded arm and cast canopy*
- Diffuser/Optics**
 - Clear tempered glass cylinder
 - Frosted glass cylinder
 - Lensed LED (no diffuser) for Dry locations only
- Light Source** LED
- Max Watts** 9.62
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations (with diffuser only) -



Ordering Guide: Choose from each category, using designated code to specify.

| | | | | | |
|-----------|----------|--------------|--------|--------|--|
| RA11 GNLX | | | | | |
| MODEL | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS | |

Diffuser/Optics

- CL** - Clear glass
- FR** - Frosted glass
- LOZ** - Lensed LED (no diffuser)

Light Source

- TL3 HO** - 3.04W/40K 982 Lm, 0-10V dimmable
- TL3** - 3.11W/30K 603 Lm, 0-10V dimmable
- TL5 HO** - 4.59W/40K 1287 Lm, 120V dimmable
- TL5** - 4.7W/30K 909 Lm, 120V dimmable
- TL6 HO** - 6.16W/40K 1588 Lm, 120V dimmable
- TL6** - 6.32W/30K 1208 Lm, 120V dimmable
- TL8 HO** - 7.75W/40K 1886 Lm, 120V dimmable
- TL8** - 7.96W/30K 1502 Lm, 120V dimmable
- TL9 HO** - 9.36W/40K 2179 Lm, 120V dimmable
- TL10** - 9.62W/30K 1790 Lm, 120V dimmable

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from [Luraline Palette](#)
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 27K** Non-Stock item - consult factory for availability
- 35K** Neutral White
- CG3** Cast aluminum guard (requires diffuser)
- DIM010** 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP** 10KV 120-277V Supplemental Surge Protection