



RLM RD11 GNA22 H: 17.25 W: 11.50 E: 27.25 MC: 7

Description

11" Deep Bowl, 22" Gooseneck arm

Specifications

| | | | |
|------------------------|---|-----|-------------|
| Housing | Spun aluminum shade with extruded arm and cast canopy | | |
| Diffuser/Optics | <ul style="list-style-type: none"> • Bare lamp (no diffuser) for Dry locations only • Clear tempered glass cylinder • Frosted glass cylinder | | |
| Light Source | GUL | MBL | Medium Base |
| Max Watts | 11 | 13 | 100 |
| Electrical | MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. MBL - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures. GUL - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver. | | |
| Mounting | Mounts over 4" recessed outlet box. | | |
| Certification | Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations (with diffuser only) - | | |



Ordering Guide:

Choose from each category, using designated code to specify.

| | | | | |
|------------|----------|--------------|--------|--------|
| RD11 GNA22 | | | | |
| MODEL | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS |

Diffuser/Optics

Bare-lamp (no diffuser)
CL - Clear glass
FR - Frosted glass

Light Source

MB25 A - 25W MAX. MED base (A19 lamp by others)
MBL6A - 5.5W/30K 470 Lm OmniLED
MBL9.8A - 9.8W/30K 800 Lm OmniLED
MBL10A JA8 - 10W/30K 800 Lm 90+ CRI OmniLED
MBL11A - 11W/30K 1100 Lm OmniLED
GUL11A - 11W/27K 1100 Lm GU24 OmniLED
MBL13A JA8 - 13W/30K 1100 Lm 90+ CRI OmniLED
MB - 100W Max Incand A (by others)

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

CG3 Cast aluminum guard (requires diffuser)