



RLM RD11 GNA22X H: 19 W: 11 E: 30 MC: 7.64

Description

11" Deep Bowl, 22" Gooseneck arm

Specifications

Housing	Spun aluminum shade with extruded arm and cast canopy*
Diffuser/Optics	<ul style="list-style-type: none"> • Clear tempered glass cylinder • Frosted glass cylinder • Lensed LED (no diffuser) for Dry locations only
Light Source	LED
Max Watts	9.62
Electrical	TL/HO- L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
Mounting	Mounts over 4" recessed outlet box.
Certification	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations (with diffuser only) -

Ordering Guide: Choose from each category, using designated code to specify.

RD11 GNA22X					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

- CL - Clear glass
- FR - Frosted glass
- LOZ - Lensed LED (no diffuser)

Light Source

- TL3 HO - 3.04W/40K 982 Lm, 0-10V dimmable
- TL3 - 3.11W/30K 603 Lm, 0-10V dimmable
- TL5 HO - 4.59W/40K 1287 Lm, 120V dimmable
- TL5 - 4.7W/30K 909 Lm, 120V dimmable
- TL6 HO - 6.16W/40K 1588 Lm, 120V dimmable
- TL6 - 6.32W/30K 1208 Lm, 120V dimmable
- TL8 HO - 7.75W/40K 1886 Lm, 120V dimmable
- TL8 - 7.96W/30K 1502 Lm, 120V dimmable
- TL9 HO - 9.36W/40K 2179 Lm, 120V dimmable
- TL10 - 9.62W/30K 1790 Lm, 120V dimmable

Finish

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded***
- RAL - Specify Color #
- UPG - Select Color from Luraline Palette
- Premium***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 27K Non-Stock item - consult factory for availability
- 35K Neutral White
- CG3 Cast aluminum guard (requires diffuser)
- DIM010 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP 10KV 120-277V Supplemental Surge Protection