



**RLM RD11 GNUX** H: 19.25 W: 11 E: 22 MC: 16.41

## Description

11" Deep Bowl, 14" U-arm

## Specifications

- Housing** Spun aluminum shade with extruded arm and cast canopy\*
- Diffuser/Optics**
- Frosted glass cylinder
  - Lensed LED (no diffuser) for Dry locations only
  - Lensed LED (no diffuser) for Dry locations only
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations (with diffuser only) -

**Ordering Guide:** Choose from each category, using designated code to specify.

RD11 GNUX				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

### Diffuser/Optics

- Lensed LED (no diffuser)
- FR** - Frosted glass
- LOZ** - Lensed LED (no diffuser)

### Light Source

### Finish

- Standard**
- BL** - Black
  - DB** - Dura-Bronze
  - WH** - White
- Upgraded\***
- RAL** - [Specify Color #](#)
  - UPG** - [Select Color from Luraline Palette](#)
- Premium\***
- CCM** - Custom Color
  - CIC** - Inner Color
  - CTC** - Clear Top Coat
- \* Subject to Surcharge

### Extras (Order Separately)

- 27K** Non-Stock item - consult factory for availability
- 35K** Neutral White
- CG3** Cast aluminum guard (requires diffuser)
- DIM010** 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP** 10KV 120-277V Supplemental Surge Protection