



**RLM RD14 GNU** H: 21.25 W: 14 E: 21.75 MC: 14.25

### Description

14" Deep Bowl, 14" U-arm

### Specifications

|                        |   |     |             |
|------------------------|---|-----|-------------|
| <b>Housing</b>         | Spun aluminum shade with extruded arm and cast canopy   |     |             |
| <b>Diffuser/Optics</b> | <ul style="list-style-type: none"> <li>• Bare lamp (no diffuser) for Dry locations only</li> <li>• Clear tempered glass cylinder</li> <li>• FR - Frosted Glass</li> </ul>   |     |             |
| <b>Light Source</b>    | GUL   | MBL | Medium Base |
| <b>Max Watts</b>       | 15  | 18  | 200         |
| <b>Electrical</b>      | <b>MB</b> - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.<br><b>MBL</b> - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.<br><b>GUL</b> - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver. |     |             |
| <b>Mounting</b>        | Mounts over 4" recessed outlet box.   |     |             |
| <b>Certification</b>   | Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations (with diffuser only)  |     |             |



**Ordering Guide:** Choose from each category, using designated code to specify.

|          |          |              |        |        |  |
|----------|----------|--------------|--------|--------|--|
| RD14 GNU |          |              |        |        |  |
| MODEL    | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS |  |

#### Diffuser/Optics

- Bare-lamp (no diffuser)
- CL - Clear glass
- FR - Frosted glass

#### Light Source

- MB25 A** - 25W MAX. MED base (A19 lamp by others)
- MBL6A** - 5.5W/30K 470 Lm OmniLED
- MBL9.8A** - 9.8W/30K 800 Lm OmniLED
- MBL10A JA8** - 10W/30K 800 Lm 90+ CRI OmniLED
- MBL11A** - 11W/30K 1100 Lm OmniLED
- GUL11A** - 11W/27K 1100 Lm GU24 OmniLED
- MBL13A JA8** - 13W/30K 1100 Lm 90+ CRI OmniLED
- GUL15A** - 15W/27K 1600 Lm GU24 OmniLED
- MBL18A JA8** - 18W/30K 1600 Lm 90+ CRI OmniLED
- MB** - Maximum 200W A (by others)

#### Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded\***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium\***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- \* Subject to Surcharge

#### Extras (Order Separately)

- CG4** Cast aluminum guard (requires diffuser)
- SSP** 10KV 120-277V Supplemental Surge Protection