



**RLM RD14 GNUX** H: 21 W: 14 E: 24 MC: 14.25

### Description

14" Deep Bowl, 14" U-arm

### Specifications

- Housing** Spun aluminum shade with extruded arm and cast canopy\*
- Diffuser/Optics**
  - Clear tempered glass cylinder
  - FR - Frosted Glass
  - Lensed LED (no diffuser) for Dry locations only
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations (with diffuser only)

**Ordering Guide:** Choose from each category, using designated code to specify.

RD14 GNUX					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

#### Diffuser/Optics

- CL - Clear glass
- FR - Frosted Glass
- LOZ - Lensed LED (no diffuser)

#### Light Source

#### Finish

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded\***
- RAL - [Specify Color #](#)
- UPG - [Select Color from Luraline Palette](#)
- Premium\***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- \* Subject to Surcharge

#### Extras (Order Separately)

- 27K** Non-Stock item - consult factory for availability
- 35K** Neutral White
- CG4** Cast aluminum guard (requires diffuser)
- DIM010** 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP** 10KV 120-277V Supplemental Surge Protection