



RLM RD9 GNA22X H: 18.75 W: 9.5 E: 28.75 MC: 7.75

Description

Specifications

- Housing** Spun aluminum shade with extruded arm and cast canopy*
- Diffuser/Optics**
 - Clear tempered glass cylinder
 - Frosted Glass cylinder
 - Lensed LED (no diffuser) for Dry locations only
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations (with diffuser only)

Ordering Guide: Choose from each category, using designated code to specify.

| | | | | | |
|-------------------|----------|--------------|--------|--------|--|
| <u>RD9 GNA22X</u> | | | | | |
| MODEL | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS | |

Diffuser/Optics

- CL - Clear glass
- FR - Frosted glass
- LOZ - Lensed LED (no diffuser)

Light Source

Finish

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded***
- RAL - Specify Color #
- UPG - Select Color from [Luraline Palette](#)
- Premium***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 27K** Non-Stock item - consult factory for availability
- 35K** Neutral White
- CG3** Cast aluminum guard (requires diffuser)
- DIM010** 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP** 10KV 120-277V Supplemental Surge Protection