



**RLM RD9 GNLX** H: 19 W: 9.5 E: 20.75 MC: 3

**Description**

**Specifications**

- Housing** Spun aluminum shade with extruded arm and cast canopy\*
- Diffuser/Optics**
  - Clear tempered glass cylinder
  - Frosted Glass cylinder
  - Lensed LED (no diffuser) for Dry locations only
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Suitable for dry or damp locations. - Suitable for wet locations (with diffuser only)

**Ordering Guide:** Choose from each category, using designated code to specify.

<u>RD9 GNLX</u>					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

**Diffuser/Optics**

- CL - Clear glass
- FR - Frosted glass
- LOZ - Lensed LED (no diffuser)

**Light Source**

**Finish**

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded\***
- RAL - Specify Color #
- UPG - Select Color from [Luraline Palette](#)
- Premium\***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**

- 27K** Non-Stock item - consult factory for availability
- 35K** Neutral White
- CG3** Cast aluminum guard (requires diffuser)
- DIM010** 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP** 10KV 120-277V Supplemental Surge Protection