



RLM RS16X P H: 19 W: 16 E: 23

Description

16" RLM, U-arm postlight (slips 3")

Specifications

- Housing** Spun aluminum shade with extruded arm and cast fitter
- Diffuser/Optics** • Bare lamp (no diffuser) for Dry locations only
• Clear glass
• Frosted Glass cylinder
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Slips 3" OD (PX Series) poles - order separately
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations (with diffuser only)

Ordering Guide: Choose from each category, using designated code to specify.

RS16X P

MODEL DIFFUSER LIGHT SOURCE FINISH EXTRAS

Diffuser/Optics

- Bare-lamp (no diffuser)
- CL** - Clear glass
- FR** - Frosted glass

Light Source

Finish

- Standard**
- BL** - Black
 - DB** - Dura-Bronze
 - WH** - White
- Upgraded***
- RAL** - [Specify Color #](#)
 - UPG** - [Select Color from Luraline Palette](#)
- Premium***
- CCM** - Custom Color
 - CIC** - Inner Color
 - CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 27K** Non-Stock item - consult factory for availability
- 35K** Neutral White
- CG3** Cast aluminum guard (requires diffuser)
- DIM010** 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP** 10KV 120-277V Supplemental Surge Protection