



**RLM RS16X P2** H: 19 W: 16 E: 43

## Description

16" RLM, Double U-arm postlight (slips 3")

## Specifications

- Housing** Spun aluminum shade with extruded arm and cast fitter
- Diffuser/Optics** • Bare lamp (no diffuser) for Dry locations only  
• Clear glass  
• Frosted Glass cylinder
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Slips 3" OD (PX Series) poles - order separately
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations (with diffuser only)

**Ordering Guide:** Choose from each category, using designated code to specify.

RS16X P2				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

### Diffuser/Optics

- Bare-lamp (no diffuser)
- CL - Clear glass
- FR - Frosted glass

### Light Source

### Finish

- Standard**
- BL - Black
  - DB - Dura-Bronze
  - WH - White
- Upgraded\***
- RAL - [Specify Color #](#)
  - UPG - [Select Color from Luraline Palette](#)
- Premium\***
- CCM - Custom Color
  - CIC - Inner Color
  - CTC - Clear Top Coat
- \* Subject to Surcharge

### Extras (Order Separately)

- 27K** Non-Stock item - consult factory for availability
- 2DIM010** LED 4-wire 0-10V Dimming - 120-277V
- 35K** Neutral White
- CG3** Cast aluminum guard (requires diffuser)
- SSP** 10KV 120-277V Supplemental Surge Protection