



**RLM RS20 GNL22X** H: 20 W: 20 E: 34 MC: 3

### Description

20" RLM, 22" L-arm

### Specifications

- Housing** Spun aluminum shade with extruded arm and cast canopy\*
- Diffuser/Optics**
  - FR - Frosted Glass
  - Lensed LED (no diffuser) for Dry locations only
- Light Source** LED
- Max Watts** 14.69
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations (with diffuser only)



**Ordering Guide:** Choose from each category, using designated code to specify.

RS20 GNL22X				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

#### Diffuser/Optics

- FR** - Frosted glass
- LOZ** - Lensed LED (no diffuser)

#### Light Source

- TL8 HO** - 7.75W/40K 1886 Lm, 120V dimmable
- TL8** - 7.96W/30K 1502 Lm, 120V dimmable
- TL9 HO** - 9.36W/40K 2179 Lm, 120V dimmable
- TL10** - 9.62W/30K 1790 Lm, 120V dimmable
- TL11 HO** - 10.99W/40K 2470 Lm, 120V dimmable
- TL11** - 11.3W/30K 2075 Lm, 120V dimmable
- TL13 HO** - 12.62W/40K 2756 Lm, 120V dimmable
- TL13** - 12.99W/30K 2352 Lm, 120V dimmable
- TL14 HO** - 14.28W/40K 3040 Lm, 120V dimmable
- TL15** - 14.69W/30K 2626 Lm, 120V dimmable

#### Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded\***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium\***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- \* Subject to Surcharge

#### Extras (Order Separately)

- 27K** Non-Stock item - consult factory for availability
- 35K** Neutral White
- CG4** Cast aluminum guard (requires diffuser)
- DIM010** 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP** 10KV 120-277V Supplemental Surge Protection