



RLM RS20 STEM H: 10 W: 20 OAL: 23.75

Description

20" RLM pendant with 12" stem and 40° swivel canopy

Specifications

Housing	Spun aluminum with extruded stem and stamped steel canopy		
Diffuser/Optics	<ul style="list-style-type: none"> • Bare lamp (no diffuser) for Dry locations only • Clear prismatic glass cylinder • Clear tempered glass cylinder • Frosted glass cylinder 		
Light Source	GUL	MBL	Medium Base
Max Watts	15	18	150
Electrical	MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. MBL - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures. GUL - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.		
Mounting	Mounts over 4" recessed outlet box.		
Certification	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations (with diffuser only)		

Ordering Guide: Choose from each category, using designated code to specify.

RS20 STEM				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

Bare-lamp (no diffuser)
CL - Clear glass
CPR - Clear prismatic glass
FR - Frosted glass

Light Source

MB25 A - 25W MAX. MED base (A19 lamp by others)
MBL11A - 11W/30K 1100 Lm OmniLED
MBL15A - 15./30K 1600 Lm OmniLED
GUL15A - 15W/27K 1600 Lm GU24 OmniLED
MBL18A JAB - 18W/30K 1600 Lm 90+ CRI OmniLED
MB - 150W Max Incand A (by others)

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

CG4 Cast aluminum guard (requires diffuser)
SSP 120 4KV 120V MOV1 Surge Suppressor

NOTES:
 *Driver is housed in extended aluminum canopy (not shown)