



RLM RS20X PR2 H: 30.50 W: 20 E: 63.50

Description

20" RLM, Double U-arm postlight (slips 4")

Specifications

- Housing** Spun aluminum shade with extruded arm and cast fitter
- Diffuser/Optics**
 - Bare lamp (no diffuser) for Dry locations only
 - Clear glass
 - Frosted Glass cylinder
- Light Source** LED
- Max Watts** 14.89 X 2
- Electrical** TL/HO- L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Slips 4" OD (PR Series) poles - order separately
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations (with diffuser only)

Ordering Guide: Choose from each category, using designated code to specify.

RS20X PR2				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

- Bare-lamp (no diffuser)
- CL** - Clear glass
- FR** - Frosted glass

Light Source

- 2TL11 HO** - 21.98W/40K 4970 Lm, 120V dimmable
- 2TL11** - 22.6W/30K 4150 Lm, 120V dimmable
- 2TL13 HO** - 25.32W/40K 5512 Lm, 120V dimmable
- 2TL13** - 25.98W/30K 4704 Lm, 120V dimmable
- 2TL14 HO** - 28.56W/40K 6080 Lm, 120V dimmable
- 2TL15** - 29.78W/30K 5252 Lm, 120V dimmable

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - [Specify Color #](#)
- UPG** - [Select Color from Luraline Palette](#)
- Premium***
- CCM** - Custom Color
- CIC** - [Inner Color](#)
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 27K** Non-Stock item - consult factory for availability
- 2DIM010** LED 4-wire 0-10V Dimming - 120-277V
- 35K** Neutral White
- CG4** Cast aluminum guard (requires diffuser)
- SSP** 10KV 120-277V Supplemental Surge Protection