



**RLM RT14 CORDX** H: 5.5 W: 14 OAL: 44

## Description

14" Tapered pendant with 36" Black 18-3 cord. (White cord supplied with white fixtures)

## Specifications

- Housing** Spun aluminum with stamped steel canopy
- Diffuser/Optics** TurboLED omni-directional silicone optic
- Light Source** LED
- Max Watts** 9.62
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - For dry locations only



**Ordering Guide:** Choose from each category, using designated code to specify.

RT14 CORDX					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

### Diffuser/Optics

**LOZ** - Omni-directional Optic

### Light Source

- TL3 HO** - 3.04W/40K 982 Lm, 0-10V dimmable
- TL5 HO** - 4.59W/40K 1287 Lm, 120V dimmable
- TL8 HO** - 7.75W/40K 1886 Lm, 120V dimmable
- TL8** - 7.96W/30K 1502 Lm, 120V dimmable
- TL9 HO** - 9.36W/40K 2179 Lm, 120V dimmable
- TL10** - 9.62W/30K 1790 Lm, 120V dimmable

### Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded\***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium\***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- \* Subject to Surcharge

### Extras (Order Separately)

- 27K** Non-Stock item - consult factory for availability
- 35K** Neutral White
- CG3** Cast aluminum guard (requires diffuser)
- DIM010** 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP** 10KV 120-277V Supplemental Surge Protection

NOTES: \*Driver is housed in extended aluminum canopy (not shown)  
 \*Driver is housed in extended aluminum canopy (not shown)  
 \*Driver is housed in extended aluminum canopy (not shown)  
 \*Driver is housed in extended aluminum canopy (not shown)  
 \*Driver is housed in extended aluminum canopy (not shown)