



RLM RT14 GNL H: 13.50 W: 14 E: 20.50 MC: 2.75

Description

14" Tapered, 14" L-arm

Specifications

Housing	Spun aluminum shade with extruded arm and cast canopy		
Diffuser/Optics	<ul style="list-style-type: none"> • Bare lamp (no diffuser) for Dry locations only • Clear tempered glass cylinder • FR - Frosted Glass 		
Light Source	GUL	MBL	Medium Base
Max Watts	11	13	100
Electrical	MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. MBL - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures. GUL - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.		
Mounting	Mounts over 4" recessed outlet box.		
Certification	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations (with diffuser only)		



Ordering Guide:

Choose from each category, using designated code to specify.

RT14 GNL				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

- Bare-lamp (no diffuser)
- CL** - Clear glass
- FR** - Frosted glass

Light Source

- MB25 A** - 25W MAX. MED base (A19 lamp by others)
- MBL6A** - 5.5W/30K 470 Lm OmniLED
- MBL9.8A** - 9.8W/30K 800 Lm OmniLED
- MBL10A JAB** - 10W/30K 800 Lm 90+ CRI OmniLED
- MBL11A** - 11W/30K 1100 Lm OmniLED
- GUL11A** - 11W/27K 1100 Lm GU24 OmniLED
- MBL11A** - 11W/30K 1100 Lm OmniLED
- MBL13A JAB** - 13W/30K 1100 Lm 90+ CRI OmniLED
- MB** - 100W Max Incand A (by others)

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- CG3** Cast aluminum guard (requires diffuser)